

Part No.

# LC20-GA2M-TX125-B1

*LC20 Vacuum/temp. gauge, 30inHg bottom, 1/4" Male NPT, 1/4" Dia x 12" long ext. probe, 5 meter cable, Bluetooth radio*

The LC20 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-GA2M-TX125-B1

## Specs/Attributes

|                           |  |
|---------------------------|--|
| Battery Count             | 2  |
| Battery Life              | 1000 Hours   |
| Battery Type              | AA Alkaline (IEC-LR6)  |
| Bluetooth Radio Installed | Yes  |
| Calibration Certificate   | ISO 17025:2017 Accredited  |
| Certifications            | Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU |
| Contains Wireless Module  | Yes  |
| Country of origin         | USA  |
| Datalogging               | PC based (via USB)   |
| Electrical Rating         | 50 mA @ 5 VDC  |
| Harmonized Code           | 9026.20.0000   |
| Ingress Protection        | IP67 (1 meter water submersion for 30 minutes)   |
| LCD Display               | 2.4 in / 61 mm segmented LCD Display   |
| Materials                 | ABS / Polycarbonate Blend, Powder Coated Aluminum  |
| Max Operating Temperature | 120 °F / 50 °C   |

## Specs/Attributes

|                             |   |
|-----------------------------|---|
| Min Operating Temperature   | -4 °F / -20 °C  |
| Panel Mount                 | No  |
| Primary Power               | Battery Power   |
| Process Connection Location | Bottom mount  |
| Protection Class            | Pollution Degree 2 (UL / IEC 61010-1)                             |
| Radio Approvals             | FCC ID 2AA9B04, IC ID 12208A-04, Japan ID 210-107153              |
| Radio Type                  | Bluetooth 5 LE  |
| Temperature Compensation    | None  |
| USB Connection              | USB (Micro B)   |
| W1 Radio Installed          | Yes   |
| Wetted Materials            | 316 Stainless Steel   |
| Wireless                    | Bluetooth   |
| Wireless Range              | 330 ft / 100 m  |
| Connector End 1             | 1/4" Male NPT (ASME B1.20.1)                                      |
| Weight                      | 12.6 oz / 355 grams   |
| Dimensions                  | H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm) |

## Sensor A (Bottom)

|                                 |   |
|---------------------------------|---|
| Engineering Units               | atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm <sup>2</sup> , mmHg @0°C, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / in <sup>2</sup>   |
| Measurement Type                | Gauge Vacuum  |
| Sensor Type                     | Pressure Sensor   |
| Max Storage Temperature         | 165 °F / 75 °C  |
| Min Operating Temperature       | -4 °F / -20 °C  |
| Min Storage Temperature         | -40 °F / -40 °C   |
| Max Vacuum                      | 30 InHg / 101.6 kPa   |
| Country of origin               | USA   |
| Burst Pressure                  | 20 PSI / 1.4 bar / 140 kPa  |
| Wrench Size                     | 7/8 In<br>23 mm   |
| Media Compatibility             | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned) |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)  |
| Wetted Materials                | 316 Stainless Steel   |
| Max Operating Temperature       | 120 °F / 50 °C  |

### Sensor A (Bottom)

|                    |                                 |
|--------------------|---------------------------------|
| Process Connection | 1/4" Male NPT                   |
| Max Pressure       | 0.00 PSI / 0.00 mbar / 0.00 kPa |

### Sensor B (Top)

|                                    |   |
|------------------------------------|---|
| Max Probe Temperature              | 300 °F / 150 °C   |
| Min Probe Temperature              | -22 °F / -30 °C   |
| Thermal Probe                      | 1/4 in / 6.35 mm diameter, 12 in / 30.5 cm long, external cable, 20 ft / 6.1 m long |
| Wetted Materials                   | 316 Stainless Steel   |
| Measurement Type                   | Temperature   |
| Media Compatibility                | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water                             |
| Accuracy - Temperature Measurement | +/- (0.15 +0.002* t ) °C (IEC 60751 Class A)  |
| Country of origin                  | USA   |
| Electrical Connection              | M12 female, A Code, Silicone seal, IP67   |
| Temperature Units                  | °C, °F, K, R  |