


Part No.

 LC20-KIT1

# LC20-KIT1

LC20-VL-VF-00 gauge, hose and adapter kit, nylon bag

## Included Items

- Pressure Gauge - LC20 pressure gauge, -15 to 300 psi bottom, -15 to 30 psi top connection, both 1/4" Male NPT (LC20-VL2M-VF2M-00)
- Hose - 1/8" Petes Plug II Probe (1/8" dia x 1.5 long) x Male Quick-test, S.S. (QTHA-PMS0-0.125-1.5)
- Adapter - 1/4" male NPT x male Quick-test, no check-valve, with cap and chain, brass (QTFT-2MB0)
- Adapter - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Adapter - 1/4" female NPT x male Quick-test, no check-valve, brass (QTHA-2FB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 6 ft (1.83 m) long (QTQT-HOS-6ft)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Case - LC10 or LC20 Pressure Gauge Case (LC-CASE)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0027)

## Pressure Gauge LC20-VL2M-VF2M-00

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Burst Pressure	1200 PSI / 83 bar / 8.30 MPa
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Max Pressure	300 PSI / 20 bar / 2.00 MPa
Min Operating Temperature	-4 °F / -20 °C
Panel Mount	No
Primary Power	Battery Power
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)

### Pressure Gauge LC20-VL2M-VF2M-00

Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Wireless	None
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

### Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.68 oz / 76 grams

### Adapter QTHA-2FB0

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N

**Adapter** QTHA-2FB0

Wrench Size	3/4 In 19 mm
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Weight	2.34 oz / 66 grams
Dimensions	H: 1.57 in (3.99 cm) x W: 0.75 in (1.91 cm) x D: 0.75 in (1.91 cm)

**Case** LC-CASE

Ingress Protection	IP67 (1 meter water submersion for 30 minutes), MIL-STD-810F
Materials	ABS Plastic, Polyethylene foam
Impact Resistance	MIL-STD-3010C
Weight	1.31 lbs / 595 grams
Dimensions	H: 9.5 in (24.13 cm) x W: 5.8 in (14.73 cm) x D: 2.8 in (7.11 cm)

**Bag** SM-0027

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 10 in (25.4 cm) x W: 2 in (5.08 cm) x D: 9 in (22.86 cm)