

Part No.

# QTFT-FRS0-VT

*5/16"-24 UNF x male Quick-test, with cap and chain, S.S., Viton seals*

Ideal for situations where frequent calibration of a DP transmitter using the bleeder port is required



QTFT-FRS0-VT

## Specs/Attributes

|                           |  |
|---------------------------|--|
| Compatible with           | Anderson Greenwood M25 Block and Bleed Valves, Anderson Greenwood M251 Block and Bleed Valves, Rosemount 2051 Series DP Pressure Transmitters, Rosemount 3051 Series DP Pressure Transmitters, Yokogawa EJ series DP Pressure Transmitters |
| Country of origin         | USA  |
| Materials                 | Stainless Steel  |
| Max Operating Temperature | 400 °F / 205 °C  |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa  |
| Media Compatibility       | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water  |
| Min Operating Temperature | -15 °F / -26 °C  |
| Seal Materials            | Viton  |
| Wrench Size               | 15 mm<br>9/16 In   |
| Connector End 1           | Male Quick-test  |
| Connector End 2           | 5/16-24 Male DP Transmitter/Gauge valve  |
| Weight                    | 1.92 oz / 54 grams   |
| Dimensions                | H: 2.7 in (6.86 cm) x W: 0.7 in (1.78 cm) x D: 0.7 in (1.78 cm)  |