

Part No.

# QTHA-ABS0

*M6 x 0.75MM x male Quick-test, no check-valve, S.S.*

Connect a Quick-test hose directly to a DP transmitter or gauge valve using the bleeder port when the transmitter is not mounted on a 3 valve manifold or gauge valve or when the manifold is not easily accessible.



QTHA-ABS0

## Specs/Attributes

Compatible with	ABB 266DSH, ABB 266DRH, ABB 266MRT, ABB 266MST
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Media Compatibility	Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	M6 X 0.75 MM Male DP Transmitter/Gauge valve
Connector End 2	Male Quick-test
Weight	0.85 oz / 24 grams
Dimensions	H: 2.16 in (5.49 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)