

Part No.

# XHGV-0000

5000 psi (350 bar) XHGV pump, 1/4" female NPT gauge swivel, 3ft hose, 1/4" MNPT process connection

Fast and efficient hydraulic field testing of pressure transmitters, gauges or switches is aided by an integral gauge adapter which allows the user to quickly attach a precision test gauge to the pump.



XHGV-0000

## Included Items

- Hand Pump - XHGV Assembly (XHGV)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Gauge Swivel - 1/4" Female NPT swivel, brass (SWIV-2FBW)

## Specs/Attributes

Max Pressure	5000 PSI
Materials	Anodized Aluminum, Brass, Plated Steel, Stainless Steel
Seal Materials	Buna-N, Delrin, Synthetic Cork, Teflon
Min Temperature	0 °F
Max Temperature	130 °F
Media Compatibility	Petroleum Based Oil, Water
Hose 1	Quick-test Hose, Brass ends, 3ft / 0.9m long
Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT